


FEATURES



USED BY

- FINANCIAL INSTITUTIONS
- SERVICE BUREAUS
- GOVERNMENT
- RETAILERS
- EDUCATION
- TRANSPORTATION COMPANIES
- HEALTHCARE

IDEAL FOR

- COMBINED DEBIT AND CREDIT CARD ISSUANCE
- CARD INSTANT ISSUANCE AT BRANCH OR STORE
- PHOTO ID CARDS
- LOYALTY CARDS
- MEMBERSHIP CARDS

SOFTWARE



INSTANT CARD software is CIM's response to the increasing demand for instant issuance of cards. Customization, flexibility and on-demand service.



MAXIMA SERIES COMBI 300 FLEXI

COMBI 300 FLEXI **LINE**

COMBI 300 FLEXI **TOWER**



A UNIQUE AND INNOVATIVE ALL-IN-ONE SOLUTION FOR CARD INSTANT ISSUANCE, THAT COMBINES EMBOSSING AND INDENTING WITH DIRECT-TO-CARD OR RETRANSFER PRINTING

Combi 300 Flexi is the only **DESKTOP SOLUTION** available today that enables you to **INTEGRATE THE EMBOSSING STATION WITH A PRINTER OF YOUR CHOICE**. Yes, that's right, any printer! CIM can configure the solution to meet your printing requirements, with the advantages of a **HEAVY DUTY MACHINE**

Combi 300 Flexi offers your customers the convenience of **INSTANTLY ISSUED CARDS** in your branches or stores. By putting a ready-to-use card directly in your customer's hand, you will visibly improve the usage and the activation rates of your cards

TWO VERSIONS AVAILABLE:

Combi 300 Flexi Tower – two level layout

Combi 300 Flexi Line – in-line layout






Embossing and indent



Vertical card transport system



In-line card transport system



6x150 cards input hoppers



Output hopper



FEATURES AND SPECIFICATIONS

CARD CAPACITY

dimensions	ISO standard CR80
thickness	0.5 to 0.8 mm - 20 to 32 mil
input hopper	Depending on the printer of your choice
output hopper	Up to 100 cards capacity
rejected cards	10 cards

EMBOSSING AND INDENTING

technology	Embossing and indenting
wheel capacity	Up to 120-character embossing and indenting wheel
indent unit	Front, rear or both sides of the card
type set	Standard Gothic (42 alphanumeric characters plus ç and ñ) for embossing OCR7B (10 numeric characters) for embossing Other font set available on request
embossing area	12 lines x 31 characters
internal tipper unit	Area 76 x 41 mm - 3 x 1.61 in. Ribbon saving feature
speed	30 seconds to emboss the card (standard layout 20-30 characters)

PRINTING OPTIONS

DEPENDING ON THE PRINTER OF YOUR CHOICE

Combi 300 Flexi Tower	for more details, please see the printer brochure
linkware Sunlight Star	for more details, please see the printer brochure
linkware TPK	for more details, please see the printer brochure
linkware HDP 5000	for more details, please see the printer brochure
other linkware on request	

Combi 300 Flexi Line	for more details, please see the printer brochure
linkware Sunlight Star	for more details, please see the printer brochure
linkware DTC 4250	for more details, please see the printer brochure
other linkware on request	

DISPLAY

Touch screen display 3.5", 320 x 240 pixel (QVGA)

COMMUNICATION & SOFTWARE

connectivity	USB 2.0 port, Ethernet (optional)
protocol	SDK available and Instant Card software
operating systems	Windows XP, VISTA, 7, 8

HARDWARE

power supply	100-117 - 220-240 Volts ; 50 to 60 Hz
temperature	10-35°C (50-95°F), 20 relative humidity 60% none condensing
physical dimensions	Depending on the printer of your choice e.g. Combi 300 Flexi Tower + printer Sunlight Star 505 W x 880 D x 585 H mm Combi 300 Flexi Line + printer Sunlight Star 1200 W x 535 D x 370 H mm (whit cover) Combi 300 Flexi Line + printer Sunlight Star 1170 W x 535 D x 370 H mm (w/out cover)
weight	Depending on the printer of your choice e.g. Combi 300 Flexi Tower + printer Sunlight Star 82 kg Combi 300 Flexi Line + printer Sunlight Star 88 kg (whit cover) Combi 300 Flexi Line + printer Sunlight Star 73 kg (w/out cover)



cimitaly.it